

Interactive Display

NEC MultiSync WD551



- Bring your own meeting (BYOM) – a simple, unified solution for instant start-up meetings using any device.
- Certified for Microsoft Teams and more – a frictionless BYOM solution launches video meetings using your preferred conferencing platform.
- Smart space management – maximise comfort of your meeting spaces and maintain optimal environmental parameters using the in-built IoT sensors to manage analytics across your meeting spaces.
- Seamless, clutter-free connection – a single secure USB-C cable connects your device with the display to auto sync the built-in camera, speakers, mic, touch and pens.
- Natural touch, easy clean – the easy to clean flush screen design reduces parallax for a superb writing experience supporting Windows Ink with two active pens included.

Specifiche

DATI MODULO DISPLAY

Tecnologia a pannello	IPS with Direct LED backlights
Risoluzione nativa (Pixel)	3840 x 2160
Dimensioni diagonali (pollici / cm)	55 / 138.78
Proporzioni	16:9
Tecnologia a retroilluminazione	LED
Luminosità (cd/m2)	400
Contrasto	1200:1
Angolo visuale (H/V)0 CR >10	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1,073 (10bit)
Response Time (typ.) [ms]	8

SPECIFICHE INTERFACCIA TATTILE

Tecnologia	PCAP
Numero di punti tattili	20
Rivestimento / filtro	Anti-glare
Resistenza schermo (H)	7
Compatibilità Sistema operativo	Android; Linux; Mac OS; Windows
Light Transmission [%]	≥ 88
Haze Level [%]	4 ~ 10
Reflection Rate [%]	4
Touch Method	Active Stylus; Conductive Passive Stylus (≥ 8 mm); Finger
Palm Rejection	No
Data Interface	USB-HID
Windows Ink	Yes

PESI E MISURE

Dimensione lunetta (S/D) mm	Edge-to-edge flush design (no bezel)
Dimensione lunetta (A/B) mm	Edge-to-edge flush design (no bezel)
Dimensioni del prodotto (L/A/S) mm	1,266 x 856.7 x 85.1
Peso del prodotto senza stand (Kg)	31.2

CONNETTIVITÀ (AUDIO/VIDEO) INPUT

HDMI	1
------	---

CAMERA

Viewing Angle [°]	120 diagonal / 113 horizontal / 81 vertical
Resolution	Output HD 3840p 30fps

SPECIFICHE CHIAVE

Special Characteristics	Collaboration Display; Microsoft Teams Certified
Operating Time	16 / 7
Altoparlanti incorporati (W)	12 W + 12 W

ALIMENTAZIONE E AMBIENTE DI FUNZIONAMENTO

Consumo di corrente (W) (funzionamento MASSIMO)	371
Temperatura operativa (oC)	+0 to +40
Umidità (%)	10 to 90

INSTALLAZIONE

Orizzontale	•
Montaggio (VESA/Numero di punti/picco mm)	4; 400 x 200 (FDMI)

CONNETTIVITÀ (DATI CONTROLLI/SERIALI)

RS232C IN	1
Porta LAN	1
USB	2

MICROPHONE/ECHO-CANCELLING

Array	built-in 6 array
Distance [m]	6
Degrees [°]	180

